



GLASS TAG Hitag S - 2.12 x 12.0 mm 134.2kHz

Chip type:	Hitag S – read / write 256 bits or 2048 bits	* Test conditions and remarks
Physical:	Diameter:	2.12 mm ± 0.15 mm
	Length:	12.0 mm ± 0.4 mm
	Weight:	95 mg
	Material:	BIO GLASS 8625
	Color:	Transparent
Electrical:	Operating frequency:	134.2 kHz ± 6 kHz * At room temperature
Chemical:	Water immersion IP68	* 20°C, 24h, 1m
	Aqueous solution of salts	* 20°C, 100h
	Alcohol, oil, HLC (10%)	* 20°C, 100h
	Ammoniac	* 20°C, 100h
Mechanical:	Vibration	IEC 68.2.6 * 6g, 14...200Hz, 3 axis, 8h/axis
	Shock	IEC 68.2.29 * 30g, 18ms, 3 axis, 1084 times/axis
Thermal:	Storage:	-40°C to + 90°C * 1 x 1000h
		+120°C * 1 x 100h
	Operating	-25°C to + 85°C
Part number:	623230 for Hitag S 256, 624230 for Hitag S 2048	

® HID reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. HID declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.
CLF 3.3.3.165 - V1 - DefKey: 3313575 - 28.10.2008 - Page: 1 of 1